



epos thermal receipt printer





www.aures.com





Thermal receipt printer with front paper feed and loading

Convenient and ultra compact, this thermal point of sale receipt printer can be easily integrated into cash desk areas.

It is one of the few in its category to be so practical and space saving and is ideal for installing sub-counter, thanks to its front paper feed and loading. The ODP 500 fits perfectly in any type of shop, store, point of service, restaurant, bar, whatever the retail or EPoS sector.

The **ODP 500** is a fast 200mm/sec; it has ESC/POS compatible drivers, automatic paper feed/loading and autocutter. It is delivered with all cables and

configuration utilities are also available.

All AURES peripherals are compatible with other EPOS systems available on the market.

ODP 500 epos thermal receipt printer

- Space saving printer thanks to front paper feed and loading (can be easily integrated / embedded into the cash desk to fit under the counter)
- Fast 200mm/sec printing
- Paper roll 80mm wide, 83mm diameter
- ESC/POS* compatible
- 5 interfaces available: Combo USB/Serial by default or USB/parallel, or USB/Ethernet, or USB/WIFI (optional)
- Configuration utilities available
- Supplied with all necessary cables

MODEL	ODP 500
Printing method	thermal
Print speed	200mm/sec
Print width	max 72mm (512 points)
Resolution	180 dpi x 180 dpi
Internal memory	64MB
Characters/lines	A: 42 columns B: 56 columns
Paper loading	automatic (from front)
THERMAL PAPER	
Width	80mm
Thickness	0.065 – 0.1mm
Roll diameter	max 83mm
CHARACTERS	
Graphic characters	128 x 18 pages
International characters	14
Barcodes	UPC – A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D: PDF 417, QR Code
Emulation	ESC/POS* compatible
Sensors	paper end
Cash drawers port	1 dual port (2 drawers)
Interfaces	Combo USB/Serial by default or USB/parallel (IEEE 1284), or USB/ Ethernet (10Mbps), or USB/WIFI (802.118) (optional)
Drivers	Windows Driver (7, XP, 2000, 2003, Vista, XP, XP Embedded) Linux, OPOS, WEPOS, JavaPOS
Auto cutter	1.5M cuts, Max 30 cuts/minute
Cut type	Total or partial cut
CHARACTERS	
Power supply	External 2 4V – 1.5 A
Colours	graphite grey
Dimensions (W x D x H)	125 x 200 x 112,52 mm
Weight	1.4kg











DIFFERENT EPOS TERMINALS