



www.aures.com



Elegant, stylish touchscreen designed especially for the world of retail, plus offering an exciting 'new' range of exclusive, up-to-the minute colours.

The OLC 15 is the first point-of-sale touchscreen to feature interchangeable colour schemes. The AURES unique modular "Clip'n Color" system, with clips in different hues, enables the device to be matched to any sales environment and maintain its visual identity.

Its refined, elegant lines, strikingly original profile and overall appearance make this touchscreen one of a kind in the POS IT market.

Retail users and staff will love its state-of-the-art design - equally attractive when viewed from in front, behind, and in profile - and so will customers paying for their purchases.

All AURES peripherals are compatible with other POS systems available on the market.



OLC15 compact and stylish

- Slimline design and compact footprint free up plenty of room on the sales counter
- Power supply unit incorporated into the base
- Tilting customer display
- Front-facing USB port
- Base supplied in 2 colours (pearl and graphite), plus 10 interchangeable colour clips
- The OLC15 is the natural companion to the Poséo Retail PC



COLOURS OF THE CLIPS

	cassis		tonic orange
	iris		carmine red
	silver		pure white
	kiwi		black piano
	mocha		indigo blue

COLOURS OF THE SYSTEM BASE

	pearl		graphite
--	-------	--	----------

MODEL

Touchscreen type	15" resistive touchscreen pad (USB interface)
LCD technology	TFT (liquid crystal display) LCD panel / display
Brightness	up to 250cd/sqm
Resolution	1024 x 768
Contrast	400 : 1
Tilt angle	0 ~ 70°

S C R E E N

OSD buttons	1 off/on button, 1 menu button, 4 screen setting buttons
On/off LED	1
USB	1 on front face

C O N N E C T I O N S

PS2	2 x PS2 (system input + keyboard output)
Serial/Com Port	1 RJ 45
USB	1 touchscreen / customer display
DC Jack	1 (12V)
Integrated power supply	30W (12V / 2.5A)
VGA	1

E N V I R O N M E N T

Safety / EMC	FCC Class A, CE, LVD
Operating temperature	+5° / +35°C
Storage temperature	-10° / +60°C
Humidity rating (in operation)	20% ~ 85% (RH without condensation)
Humidity rating (in storage)	5% ~ 90% (RH without condensation)
Customer display	VFD Display (USB interface) 2 lines x 20 characters
Dimensions (W x D x H)	419 x 310 x 253 (up to 332)mm
Weight	6kg

O P T I O N S

Magnetic card reader	3-track (RS 232 or keyboard interface)
Optional internal loudspeakers	2 x 2W



Customer Display



Optional card/Dallas reader or RFID reader



Integrated power supply adapter