

promotional VESA-mount touchscreen



www.ares.com



Promotional touchscreen for wall mounted or dual screen applications.

This tilting 8.4" touchscreen (220 x 175mm overall) is equipped with VESA standard fixings and becomes the ideal product to display customer targeted messages and enhance the retail experience at the till point.

It can be used alone in wall mounted applications, or in dual screen installations, fixed on a pole or an arm. It's ideal to mount behind the OLC 15V

touchscreen and has been designed to display interactive images, texts, adverts and commercials geared at waiting and paying customers during cash desk operations.

OLC 8.4V is supplied with a dual-capability cable (for power and video), allowing direct power supply from a retail PC such as the Poséo 5200, also available in non-touch version.



OLC 8.4V promotional touchscreen



OLC 15V

OLC 8.4V

MODEL

OLC 8.4-V

Touchscreen	Turbo Touch resistive
Panel size	8.4"
Brightness	250nits / 250cd/m2
Resolution	800 x 600

EXTERNAL I/O PORTS


DC-in Jack	1 x (12V)
VGA	1
Power button	1
OSD buttons	1 x Power button for LCD monitor on/off 1 x Menu button to get into video set up mode 1 x up/down button for video function adjustment purpose 1 x Exit button

POWER


Power source	External 30W adapter, 12V/2.5A
Dual power supply cable	VGA cable + power supply in one cable

ENVIRONMENT

EMC & Safety	CE, FCC Class A, LVD
Operating temperature	0-40°C
Storage temperature	-20 – 60°C
Operating humidity	20% to 80% RH, non condensing
Storage humidity	20% to 85% RH, non condensing
Colors	perle or graphite
Dimensions (W x H x D)	220 x 175 x 41.4 mm overall
Weight	0.9kg
Mounting	75 x 75 VESA standard



with Odysse II



with OLC15



VESA holdings

Specifications are subject to change without notice

www.aures.com

MANUFACTURER OF REMARKABLY
DIFFERENT EPOS TERMINALS

AURES